

SURFACE MOUNTED LIGHTS

PANEL LIGHT MR



|                               |                   |
|-------------------------------|-------------------|
| WATTAGE                       | INPUT VOLTAGE     |
| <b>0.96</b> Watt              | <b>12</b> Volt DC |
| CORRELATED COLOUR TEMPERATURE |                   |
| <b>3000 / 6000</b> Kelvin     |                   |

TECHNICAL DATA

|                                                                     |                                                                     |
|---------------------------------------------------------------------|---------------------------------------------------------------------|
| Input voltage                                                       | <b>12 Volt DC</b>                                                   |
| Wattage                                                             | <b>0.96 Watt</b>                                                    |
| Type                                                                | <b>2000 mm mains lead with LED plug</b>                             |
| Dimensions                                                          | <b>125 x 66 x 6 mm</b><br><b>further sizes and types on request</b> |
| Housing colour                                                      | <b>white / aluminium</b>                                            |
| Installation                                                        | <b>on / off tape or double adhesive tape</b>                        |
| Correlated colour temperature and luminous flux of the light source | <b>3000K   76 Lumen</b><br><b>6000K   78 Lumen</b>                  |
| Lumen maintenance factor                                            | <b>L70B50 &gt;36000 h</b>                                           |
| CRI                                                                 | <b>90</b>                                                           |
| EEC                                                                 | <b>G</b>                                                            |
| Waste disposal                                                      | <b>through suitable disposal site</b>                               |
| Replaceability                                                      | <b>the light source is not replaceable</b>                          |

Subject to technical modifications. Special lengths and customized versions are available upon request.

VARIANTS

| ORDER NO.    | LIGHT COLOUR                                                                            |                    |
|--------------|-----------------------------------------------------------------------------------------|--------------------|
| 32.840.031ww |  3000K | warm white · 76 lm |
| 32.840.031cw |  6000K | cold white · 78 lm |

DIMENSIONAL DRAWING

